

H-sjakk med mutterbolt – ANJA Offshore

856

H-sjakk med mutterbolt



Materiale	Varmebehandlet og herdet, høylegert stål, grade 8
Overflatebehandling	Varmgalvanisert
Min. temp.	-40°C
Max. temp.	+200°C

Art.nr.	WLL	SF	a	b	d	d1	d2	e
0310606	2.0 T	8:1	21 mm	47 mm	13 mm	16 mm	33 mm	33 mm
0310607	3.25 T	8:1	27 mm	60 mm	16 mm	19 mm	40 mm	42 mm
0310608	4.75 T	8:1	31 mm	71 mm	19 mm	22 mm	47 mm	51 mm
0310609	6.5 T	7,8:1	37 mm	84 mm	22 mm	25 mm	52 mm	58 mm
0310610	8.5 T	7,2:1	43 mm	95 mm	25 mm	28 mm	58 mm	68 mm
0310611	9.5 T	6,9:1	46 mm	108 mm	28 mm	32 mm	64 mm	74 mm
0310612	12.0 T	6,4:1	52 mm	119 mm	32 mm	35 mm	72 mm	83 mm
0310613	13.5 T	6,1:1	57 mm	132 mm	35 mm	38 mm	74 mm	89 mm
0310614	17.0 T	6:1	60 mm	146 mm	38 mm	42 mm	84 mm	98 mm
0310615	25.0 T	6:1	74 mm	178 mm	45 mm	50 mm	105 mm	127 mm
0310616	35.0 T	6:1	83 mm	197 mm	50 mm	57 mm	119 mm	138 mm
0310618	55.0 T	6:1	105 mm	255 mm	65 mm	70 mm	145 mm	185 mm



Les mer om produktet her:

<https://john-dahle.no/product?number=VM-0310606>