

Sveisbart løfteøre med fjær – APAS


- Materiale: Øye i grade 10-materiale, sveisefeste i S355J2.
- Overflatebehandling: Blålakkert øye og ubehandlet sveisefeste.



Min. temp. -20°C

Max. temp. +200°C

Art.nr.	WLL	SF	a	b	h	s1	s2	t	w	Vekt
0362080	1.4 T	4:1	35 mm	37 mm	41,5 mm	15,0 mm	13,5 mm	69,5 mm	39,5 mm	0.4 kg
0362082	2.5 T	4:1	40 mm	40 mm	47,0 mm	16,0 mm	14,0 mm	77,5 mm	45 mm	0.6 kg
0362084	4.0 T	4:1	45 mm	48 mm	52,0 mm	19,0 mm	17,5 mm	86,0 mm	50 mm	0.9 kg
0362086	6.7 T	4:1	53 mm	60 mm	61,5 mm	25,5 mm	22,0 mm	103,0 mm	60 mm	1.8 kg
0362088	10.0 T	4:1	63 mm	74 mm	72,0 mm	29,5 mm	26,0 mm	126,0 mm	70 mm	3.0 kg
0362090	16.0 T	4:1	90 mm	92 mm	102,0 mm	38,0 mm	34,0 mm	168,5 mm	100 mm	6.7 kg
0362092	20.0 T	4:1	100 mm	104 mm	112,0 mm	44,5 mm	40,0 mm	189,0 mm	110 mm	10.0 kg



Les mer om produktet her:

<https://john-dahle.no/product?number=VM-0362080>