

Strut profile 40x80L 6 m

Art.no.: 2401-3842529341

Extra strong aluminum profile from Rexroth with L-design for maximum strength. Ideal for large modular constructions, frames, and industrial applications. Supplied in 6070 mm length.

The Rexroth strut profile 40x80L is made of natural anodized aluminum, providing excellent strength and flexibility. Features slots for easy attachment of accessories and components, making it perfect for frame building, machine construction, and heavy-duty structures. Dimensions: 40x80 mm. Length: 6070 mm. Material: Aluminum



Color	Natural
Material	Aluminum, anodized
Modular dimension	40 mm
Cross-section	40x80L
Profile slot	10.0
Open slots	6.0
Profile type	Standard
Dimensions	40x80
ESD	true
Area moment of inertia in y-direction [I _y]	17.3 cm
Moment of resistance in the x-direction [W _x]	8.7 cm ³
Area moment of inertia in x-direction [I _x]	63.4 cm
Moment of torsion resistance [W _t]	4.8 cm ³
Moment of resistance in the y-direction [W _y]	15.9 cm ³
Torsional moment of inertia [I _t]	8.02 cm
Length [L]	6070 mm
Mass [m]	2.7 kg/m
Profile surface [A]	9.9 cm ²
Brand	rexroth
HS code	76042100
COO	NLD

Sales unit: PCS


Master packaging (pcs) 12



40x80L

A = 9,9 cm²
I_x = 63,4 cm⁴
I_y = 17,3 cm⁴
W_x = 15,9 cm³
W_y = 8,7 cm³
I_t = 8,02 cm⁴
W_t = 4,8 cm³
m = 2,7 kg/m

19210



Read more about the product here:

<https://john-dahle.no/product?number=2401-3842529341>