

Strut profile 20x20 2N 3 m

Art.no.: 2401-3842536478

Compact and durable aluminum profile from Rexroth with 2N slots. Ideal for modular constructions, frames, and machine building. Supplied in 3-meter length with high precision.

The Rexroth strut profile 20x20 mm 2N is a natural anodized aluminum profile featuring slots for easy attachment of accessories and components. Provides excellent stability and flexibility for industrial applications. Dimensions: 20x20 mm. Length: 3000 mm. Material: Aluminum.




Color	Natural
Material	Aluminum, anodized
Brand	rexroth
HS code	76042100
COO	SWE
Sales unit:	PCS
Master packaging (pcs)	20
Modular dimension	20 mm
Cross-section	20x20 2N
Profile slot	6.0
Open slots	2.0
Profile type	2N
Dimensions	20x20
Area moment of inertia in y-direction [I _y]	0.8 cm
Moment of resistance in the x-direction [W _x]	0.8 cm ³
Area moment of inertia in x-direction [I _x]	0.7 cm
Moment of torsion resistance [W _t]	0.52 cm ³
Moment of resistance in the y-direction [W _y]	0.7 cm ³
Torsional moment of inertia [I _t]	0.31 cm
Length [L]	3000 mm
Mass [m]	0.5 kg/m
Profile surface [A]	1.8 cm ²



20x20 2N

A = 1,8 cm²
I_x = 0,7 cm⁴
I_y = 0,8 cm⁴
W_x = 0,7 cm³
W_y = 0,8 cm³
I_t = 0,31 cm⁴
W_t = 0,52 cm³
m = 0,5 kg/m

19870



Read more about the product here:

<https://john-dahle.no/product?number=2401-3842536478>