


Strut profile 30x30 6 m

Art.no.: 2401-3842990720

Strong aluminum profile from Rexroth with high precision. Ideal for modular constructions, frames, and industrial applications. Supplied in 6-meter length for larger projects.

The Rexroth strut profile 30x30 mm is made of natural anodized aluminum, providing excellent strength and flexibility. Features slots for easy attachment of accessories and components, making it perfect for frame building and machine construction. Dimensions: 30x30 mm. Length: 6000 mm. Material: Aluminum.




Modular dimension	30 mm
Profile type	Standard
Moment of torsion resistance [Wt]	0.33 cm ³
Profile surface [A]	3.1 cm ²
Mass [m]	0.9 kg/m
Length [L]	6000 mm
Dimensions	30×30
Cross-section	30×30
Profile slot	8.0
Torsional moment of inertia [It]	0.29 cm
Open slots	4.0
Area moment of inertia in x-direction [Ix]	2.8 cm
Area moment of inertia in y-direction [Iy]	2.8 cm
Moment of resistance in the y-direction [Wy]	1.8 cm ³
Moment of resistance in the x-direction [Wx]	1.8 cm ³
Color	Natural
Material	Aluminum, anodized
Brand	rexroth
HS code	0
COO	-
Sales unit:	PCS

Master packaging (pcs) 20

30x30
A = 3,1 cm²
I_x = 2,8 cm⁴
I_y = 2,8 cm⁴
W_x = 1,8 cm³
W_y = 1,8 cm³
I_t = 0,29 cm⁴
W_t = 0,33 cm³
m = 0,9 kg/m

10170



Read more about the product here:

<https://john-dahle.no/product?number=2401-3842990720>